

DESCRIPCIÓN

Esmalte SloanTec®, Cerámica Piso-Montado Pressure Assisted Water Closet.

COMPONENTES

- Bowl: Code 2178009
- Tank: Code 2108016

DETALLES

- Flush Volume: 1.0 gpf (3.8 Lpf)

CARACTERÍSTICAS

- Permanent SloanTec® hydrophobic antimicrobial glaze inhibits the growth and buildup of germs, bacteria, mold, mildew and mineral scale on the surfaces
- Elongated bowl
- Floor mounted, floor outlet
- 12" (305mm) rough-in
- Chrome metal flush handle
- Secure, anti-rocking 3-point tank mounting system
- Powered by Flushmate® brand pressure assisted flushing technology to achieve 1,000g MaP score
- Over 60 ft (18.3 m) drainline carry performance
- Water spot area: 11 ¼ x 9¾ (286 mm x 248 mm)
- Smooth, quiet cable activated flush handle - left hand
- Closet bolts and caps included
- Toilet seat and wax ring not included

REQUERIMIENTOS DE SISTEMA DE PLOMERÍA

- Maximum Static Pressure: 80 PSI (552 kPa)
- Minimum Static Pressure: 25 PSI (172 kPa)

DESCARGAS

- [Pressure-Assisted Installation Instructions](#)
- [Flushmate Owner's Manual](#)
- [Pressure-Assisted Repair and Maintenance Guide](#)
- [Descargas Adicionales](#)



CUMPLIMIENTOS Y CERTIFICACIONES



(Certificado cUPC Ecológico, Listado por WaterSense, Cumple con CALGreen , Cumple con CEC, NOM Certified)

NOTAS

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

Toda la información contenida dentro de este documento está sujeta a cambio sin previo aviso.

PREPARACIÓN

